

# SUPERtrol-I

## Multi-Function Flow Totalizer, Ratemeter and Batcher

### Features

- "EZ Setup" Guided Setup for First Time Users
- Rate/Total and Batching Functions
- Menu Selectable Hardware & Software Features
- Environmental Compliance Monitoring and Report Generation
- Universal Viscosity Curve (UVC) and API Eq.
- Advanced Batching Features: Overrun Compensation, Autobatch Start, Print End of Batch, Slow Fill, 2 Stage Batching
- Isolated Outputs Standard
- RS-232 Port Standard, RS-485 Optional  
Advanced Printing Capabilities  
Windows™ Setup Software
- DIN Enclosure with Two Piece Connectors
- On Board Data Logging
- DDE Server & HMI Software Available
- Enhanced Modem Features for Remote Metering
- NEW! - Attractive Wall Mount Enclosure

### Description:

The SUPERtrol-I Flow Computer satisfies the instrument requirements for a variety of flowmeter types in liquid applications. Multiple flow equations and instrument functions are available in a single unit with many advanced features.


The alphanumeric display shows measured and calculated parameters in easy to understand format. Single key direct access to measurements and display scrolling is supported

The versatility of the SUPERtrol-I permits a wide measure of versatility within the instrument package. The various hardware inputs and outputs can be "soft" assigned to meet a variety of common application needs. The user "soft selects" the usage of each input/output while configuring the instrument.

The isolated analog output can be chosen to follow volume flow, corrected volume flow, mass flow, temperature, or density by means of a menu selection. Most hardware features are assignable by this method.

The user can assign the standard RS-232 Serial Port for data logging, transaction printing, or for connection to a modem for remote meter reading.

A Service or Test mode is provided to assist the user during start-up system check out by monitoring inputs and exercising outputs and printing system setup.



### Specifications:

#### Flow Meters and Computations

Meter Types: All linear and square law meters supported including: vortex, turbine, magnetic, PD, target, orifice, venturi, v-cone and many others  
Linearization: Square root, 16 point table or UVC table  
Computations: Volume, Corrected Volume & Mass  
Fluid Computations: Temperature, Density, Viscosity and API 2540 for petroleum.

#### Environmental

Operating Temperature: 0°C to +50°C  
Storage Temperature: -40°C to +85 C  
Humidity : 0-95% Non-condensing  
Materials: U.L. approved

**Listing:** UL Listed (File No. E192404), CE Approved, CSA Pending

#### Display

Type: 2 lines of 20 characters  
Types: Backlit LCD and VFD ordering options  
Character Size: 0.3" nominal  
User programmable label descriptors and units of measure

#### Keypad

Keypad Type: Membrane Keypad with 16 keys

#### Enclosure

Size: See Dimensions  
Depth behind panel: 6.5" including mating connector  
Type: DIN  
Materials: Plastic, UL94V-0, Flame retardant  
Bezel: Textured per matt finish

#### Real Time Clock

The SUPERtrol-I is equipped with a battery backed real time clock with display of time and date.

#### Format:

12 or 24 hour time display  
Day, Month, Year date display

#### Power Input

The factory equipped power option is internally fused. An internal line to line filter capacitor and MOV are provided for added transient suppression.

110 VAC Power: 85 to 127 Vrms, 50/60 Hz (11.0 VA)  
220 VAC Power: 170 to 276 Vrms, 50/60 Hz (11.0 VA)  
DC Power:

12 VDC (10 to 14 VDC); 300 mA max.  
24 VDC (14 to 28 VDC); 300 mA max.

## Flow Inputs:

### Analog Input:

Accuracy: 0.01% FS at 20° C

#### Ranges

Voltage: 0-10 VDC, 0-5 VDC, 1-5 VDC

Current: 4-20 mA, 0-20 mA

Basic Measurement Resolution:

16 bit

Update Rate: 4 updates/sec

Automatic Fault detection: Signal over/under-range,  
Current Loop Broken

Calibration: Software Calibration (no trimmers) and  
Auto-zero Continuously

Extended calibration:

Learns Zero and Full Scale of each range using  
special test mode.

Fault Protection:

Reverse Polarity: No ill effects

Over-Voltage Limit: 50 VDC Over voltage  
protection

Over-Current Protection: Internally current limited  
protected to 24VDC

### Pulse Inputs:

Number of Flow Inputs: one with or without quadrature

Input Impedance: 10 K $\Omega$  nominal

Pullup Resistance: 10 K $\Omega$  to 5 VDC (menu selectable)

Pull Down Resistance: 10 K $\Omega$  to common

Trigger Level: (menu selectable)

High Level Input

Logic On: 3 to 30 VDC

Logic Off: 0 to 1 VDC

Low Level Input (mag pickup)

Sensitivity:

10 mV or 100 mV

Minimum Count Speed:

Menu selectable

Maximum Count Speed:

Menu Selectable: 40Hz, 3000Hz or 20 kHz

Overvoltage Protection: 50 VDC

### Auxiliary / Compensation Input

The auxiliary/compensation input is menu selectable for temperature, density or not used. This input is used for the compensated input when performing compensated flow calculations. It can also be used as a general purpose input for display and alarming.

Operation: Ratiometric

Accuracy: 0.01% FS at 20° C

Basic Measurement Resolution:

16 bit

Update Rate: 1 update/sec minimum

Automatic Fault detection:

Signal Over-range/under-range

Current Loop Broken

RTD short

RTD open

Fault mode to user defined default settings

Fault Protection:

Reverse Polarity: No ill effects

Over-Voltage Limit (Voltage Input): 50 VDC

Available Input Ranges

Voltage: 0-10 VDC, 0-5 VDC, 1-5 VDC

Current: 4-20 mA, 0-20 mA

Resistance: 100 Ohms DIN RTD

100 Ohm DIN RTD

(DIN 43-760, BS 1904):

Three Wire Lead Compensation

Internal RTD linearization learns ice point resistance

1 mA Excitation current with reverse polarity  
protection

Temperature Resolution: 0.01 C

### Control Inputs

Switch Inputs are menu selectable for Start, Stop, Reset,  
Lock, Inhibit, Alarm Acknowledge, Print or Not Used.

Control Input Specifications

Input Scan Rate: 10 scans per second

Logic 1: 4 - 30 VDC

Logic 0: 0 - 0.8 VDC

Input Impedance: 100 K $\Omega$

Control Activation:

Positive Edge or Pos. Level based on product  
definition for switch usage.

### Excitation Voltage

Menu Selectable: 5, 12 or 24 VDC @ 100 mA (fault  
protected)

### Relay Outputs

The relay outputs are menu assignable to (Individually  
for each relay) Low Rate Alarm, Hi Rate Alarm, Prewarn  
Alarm, Preset Alarm or General purpose warning  
(security), low temperature/high temperature.

Number of relays: 2 (4 optional)

Contact Style: Form C contacts

Contact Ratings: 5 amp, 240 VAC or 30 VDC

### Serial Communication

The serial port can be used for printing, datalogging,  
modem connection and communication with a computer.  
RS-232:

Device ID: 01-99

Baud Rates: 300, 600, 1200, 2400, 4800, 9600,  
19200

Parity: None, Odd, Even

Handshaking: None, Software, Hardware

Print Setup: Configurable print list and formatting.

Print Out: Custom form length, print headers,  
print list.

Print Initialization: Print on end of batch, key  
depression, interval, time of day or  
remote request.

RS-485:

Device ID: 01-247

Baud Rates: 300, 600, 1200, 2400, 4800, 9600,  
19200

Parity: None, Odd, Even

Protocol: Modbus RTU (Half Duplex)

### Data Logging

The data logger captures print list information to internal  
storage for approximately 1000 transactions. This  
information can be used for later uploading or printing.  
Storage format is selectable for Comma-Carriage Return  
or Printer formats.

